



US006214400B1

(12) **United States Patent**
Zittel et al.

(10) **Patent No.:** **US 6,214,400 B1**
(45) **Date of Patent:** **Apr. 10, 2001**

(54) **METHOD FOR PROCESSING FOOD PRODUCT**

(75) Inventors: **David R. Zittel**, Columbus; **Steven W. Hughes**, Beaver Dam; **Daniel D. Mauplin**, Columbus, all of WI (US)

(73) Assignee: **Lycio Manufacturing Inc.**, Columbus, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/419,716**

(22) Filed: **Oct. 14, 1999**

(51) Int. Cl.⁷ **A23L 1/00**

(52) U.S. Cl. **426/509; 426/510; 426/511; 426/520**

(58) Field of Search **426/509, 510, 426/511, 520, 523; 99/348, 404, 409, 479, 516, 536**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,238,997	*	12/1980	Hengstenberg	99/348
4,875,344		10/1989	Zittel	62/381
4,942,810		7/1990	Zittel et al.	99/477
5,133,249		7/1992	Zittel	99/348
5,146,841	*	9/1992	Zittel	99/348
5,327,817		7/1994	Zittel	99/348
5,329,842		7/1994	Zittel	99/348
5,341,729		8/1994	Zittel	99/348
5,427,015		6/1995	Zittel	99/348
5,429,041		7/1995	Zittel	99/348
5,456,091		10/1995	Zittel	62/375

5,517,906	5/1996	Zittel et al.	99/536
5,587,073	12/1996	Zittel	210/372
5,592,869	1/1997	Zittel	99/348
5,632,195	5/1997	Zittel	99/348
5,669,288	9/1997	Zittel et al.	99/348
5,752,431	5/1998	Zittel	99/348
5,780,088	7/1998	Zittel et al.	426/483
5,809,787	9/1998	Zittel	62/63

* cited by examiner

Primary Examiner—George C. Yeung

(74) *Attorney, Agent, or Firm*—Nilles & Nilles SC

(57) **ABSTRACT**

A method and rotary blancher for processing food product using a heat transfer medium and directed flows of a fluid that can comprise a liquid, a gas, a vapor or a combination thereof. The directed flows can be discharged from orifices or banks of orifices that are distributed around the food products in the blancher. The flows are discharged at a high flow rate, a high pressure, or a combination of both. Where a liquid is discharged, it preferably is discharged at a flow rate of at least 20 gpm and at least 30 psi. Where a gas is discharged, it is discharged at a flow rate of at least 60 CFM at a pressure of at least 2 psi or at a flow rate of at least 10 CFM at a pressure of at least 80 psi. If desired, discharged fluid can be recirculated to save energy. To help increase agitation and help break up clumps of food products in the blancher, direct-contact mechanical agitation devices, such as baffles, can be used. Such a blancher and method can be used to process food product by blanching, cooking and pasteurizing, is suited for processing relatively heavy food products having a density of at least 55 lbs/ft³ using discharged liquid and gas, and is suited for processing food products having a lesser density using only discharged gas.

40 Claims, 9 Drawing Sheets

